

# Waist High Turnstile

## DSPT Series *Interior & Exterior Application*

The DSPT Series is ideal in demanding situations where you want a more open, stylish look. It is made for years of reliable service in high traffic/high volume applications. The cabinets are constructed of heavy 14-gauge, 300 series stainless steel and feature our versatile 6500 Series Control Head. This unit features our longest turnstile arm and is suited for indoor or outdoor installations.



**DSPT SERIES**



## FEATURES AND BENEFITS

- Bidirectional key overrides
- Daylight visible indicator lights
- 8 digit key resetable LCD counter with seven year lithium battery
- Rubber arm covers
- Coin/token acceptor
- Bill acceptor
- Ticket drop box
- Additional options available on request
- Round end design with solid surface top
- Square end design with stainless steel top

### Solid Surface Top:

These are just a few of the solid surfaces available for your turnstile's custom top.



**DSI**<sup>®</sup>  
DESIGNED SECURITY, INC.  
*Building Security*

1402 Hawthorne St.  
Bastrop, TX 78602  
Voice: 1-800-272-3555  
Fax: 1-512-321-9181  
E-mail: [dsi@dsigo.com](mailto:dsi@dsigo.com)  
[www.dsigo.com](http://www.dsigo.com)

# DSPT Series - Interior & Exterior Application

## Applications:

This series is made for years of reliable service in high traffic / high volume environments where a more open, stylish look is desired.

## Product Features:

### Cabinets are finished in:

- Our signature 304 stainless steel/ No. 4 satin finish

### Design & Construction:

- Designed for secure and reliable operation with aesthetics in mind
- Cabinet inner and outer shells and cover are constructed of (14 gauge) 304 stainless steel / No. 4 satin finish
- Arms assembly constructed with 1 5/16" (33mm) diameter, (12 gauge) stainless steel
- Hub 4 1/2" (114mm) o.d. also made from stainless
- Minimal exposed hardware

### Measures:

- Height: 38" (965mm)
- Width: 48.25" (1226mm)
- Depth: 10.25" (260mm)

## Operation:

### Control Head, featuring:

- Auto-indexing (self-centering) with adjustable hydraulic shock suppression
- Hardened tool steel locking bars, cam and roller assemblies
- Permanently lubricated bearings • Your choice of manual or electronic control on both directions
- Nearly universal integration to any number of access control systems
- Your choice on each electronic direction of locking or unlocking on power failure

### Options:

- Bidirectional key overrides
- Daylight visible indicator lights
- 8 digit key resetable LCD counter with seven year lithium battery
- Rubber arm covers
- Coin/token acceptor
- Bill acceptor
- Ticket drop box
- Additional options available on request
- Round end design with solid surface top
- Square end design with stainless steel top

## Electrical Specifications:

Input Voltage: 100-240 VAC  
Input Current: 1.3 - .55 A  
Frequency: 50/60 Hz  
Storage Temperature: -4 to 158°F  
Operating Temperature: 32 to 122°F  
Operating Voltage: 24VDC  
Operating Current: 1.2 A (typical)

## Standards and Codes:

Austenitic stainless steel:  
ASTM A240, A249, A276  
Hot rolled steel:  
AISI C-1020, AISI C-1018  
Hot dipped galvanizing:  
ASTM A-143, ASTM A-153-80  
Stainless steel fasteners:  
ASTM A-320  
American Welding Society (AWS)  
Standard D 1.1

## Warranty:

Units are warranted against defects in materials and workmanship for a period of one year from date of invoice.



1402 Hawthorne St.  
Bastrop, TX 78602  
Voice: 1-800-272-3555  
Fax: 1-512-321-9181  
E-mail: dsi@dsigo.com  
www.dsigo.com

